

Premium Acrylic Masonry Waterproofer

CCI Dri-Look™ is a very unique and state-of-the-art brick and silicone free masonry waterproofing product designed to provide a long lasting water resistant finish yet leaves the natural look of the surface as though there was nothing there!

Features – Water Resistant Yet Invisible – Very low VOC – Interior or Exterior – No Odor or Silicones!

DESCRIPTION

CCI Dri-Look™ is a superior acrylic sealer that utilizes Micronized Wax technologies to accomplish an invisible water resistant barrier that allows the material to “wet out”, yet will not allow penetration into the substrate to induce deterioration and degradation. Because it is invisible, the natural look of the brick or stone is retained keeping it water resistant without the shiny look common to most waterproofing products.

USES

CCI Dri-Look™ can be used on interior or exterior masonry and concrete-type surfaces including natural or manufactured stone and precast products. It is perfect for commercial or residential applications and is ideal for areas where exposure to rain or water will be an issue. It is extremely economical to use, and dries very quickly. This allows quick turnaround times. CCI Dri-Look™ is not recommended for horizontal traffic surfaces, granite or marble.

PACKAGING

CCI Dri-Look™ is available in one-gallon (3.785 L), five-gallon (18.925 L) and fifty-five gallon (209 L) containers.

COVERAGE

CCI Dri-Look™ will cover approximately 500 to 600 square feet per gallon depending upon the porosity of the surface and the application method. Spraying is recommended to maintain a natural look. Roll applications of Dri-Look™ can result in a thicker film build and will be shiny. The first spray application is invisible. Subsequent applications will begin to accomplish a surface that is shinier with each application.

STORAGE

Store in a safe place. Keep containers tightly sealed. DO NOT allow product to freeze. Material that is frozen CANNOT be used when thawed. Shelf life is approximately 12 months.

CAUTIONS

Must be applied as a very thin film. Not recommended for use in areas of standing water or prolonged dampness. KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Material Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product. Safety glasses or goggles are recommended particularly for spray applications.

EQUIPMENT FOR APPLICATION

Sprayer: Larger applications are usually done with a high quality garden-type pump sprayer. For small or inaccessible areas, a good quality brush may be used.

PREPARATION OF CONCRETE

The surface should be cured at least 28 days, prior to application. The newly sealed application area must be completely clean and dry to the touch. Pressure washing and power scrubbing may be necessary. Remove all efflorescence, oil, dirt, wax, old paints, sealers, and curing compounds. RINSE THOROUGHLY. Allow the surface to dry at least 24 hours. Soaps and detergents should not be used for cleaning unless stain removal makes them necessary. Dried soap residue on the surface will prevent the wax from bonding. Do not use where hydrostatic pressure is possible.

APPLICATION

Always test a small area of surface to verify protection and appearance. Apply in temperatures between 12.8 °C to 26.7 °C (55°F and 80°F). For best results, Apply Dri-Look™ using a pump sprayer in thin even applications. Apply a thin, light, even coat over the entire surface (emphasis on the word **film**, not coat). **CAUTION: DO NOT FLOOD COAT OR USE A ROLLER TO APPLY DRI-LOOK™.** Dri-Look™ is a thin film product and is designed to be applied at 2-4 wet mils (400-800 ft²/gal) Applied material will be slightly milky and should become transparent within a few minutes. If this is not the case, the material is being applied too heavily and the area must be immediately rinsed off or allowed to dry, then reapplied once the surface is dry. Surface will look wet for a few minutes and then will dry to transparent. Allow 30 minutes to dry between coats. Apply each coat in the same manner. If a lightly higher sheen is desired, wait 2-4 hours and apply another application. Keep in mind that after the initial application, the surface will become shiner with each application. One generous application is typically all that is necessary to provide water resistance. If applied correctly, the surface will look unsealed, but will have all the necessary protection that is required.

MAINTENANCE

The sealed surface should be inspected periodically to ensure long term protection. Inspect by deluging the surface and checking for it to become dry after a minute or so. Areas that stay wet for more than a few minutes may need a fresh application. Allow the surface to dry before resealing.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

PLAN SPECIFICATION

CCI Dri-Look™ Suggested Short Form Specification:

All surfaces to be sealed and maintained in the plans and specifications shall be treated with 1-2 light even coats of CCI Dri-Look™, manufactured by CCI 800-443-2871, Layton, UT. CCI Dri-Look™ shall be applied in accordance with the CCI Dri-Look™ Technical Information Sheet.

ORDER SPECIFICATION

Product: CCI Dri-Look™		
Shipping Weight: 9 lbs (4.05 kg)	Container Size: 1-Gallon (3.785 L)	Item No: S-DRILK-1
Shipping Weight: 45 lbs (20.25 kg)	Container Size: 5-Gallon (18.925 L)	Item No: S-DRILK-5
Shipping Weight: 450lbs (202.5 kg)	Container Size: 55-Gallon (208.175L)	Item No: S-DRILK-55

"Concrete Coatings Inc., warrants its products to be free of manufacturing defects and that they will meet Concrete Coatings Inc. current published physical properties when applied in accordance with Concrete Coatings Inc. written directions and tested in accordance with ACI, ASTM and Concrete Coatings Inc. Standards. There are no other warranties by Concrete Coatings Inc. of any nature whatsoever, expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. Concrete Coatings Inc. shall not be liable for damages of any sort, including remote or consequential damages, resulting from any claimed breach of any warranty, whether expressed or implied, from any other cause whatsoever. Concrete Coatings Inc. will not be responsible for use of this product in a manner to infringe on any patent held by others. User assumes all liability and risk associated with use, selection, application and warranty of product. Concrete Coatings Inc. makes no representation as to the suitability of product for any application and/or damages of any kind directly or indirectly associated with its selection or application."

For the Location of Your Nearest Concrete Coatings Inc. Representative
CALL NATIONWIDE TOLL-FREE 1-800-443-2871