

VIVIDTM Acid Stain MATERIAL SAFETY DATA SHEET

Page 1 of 4 Effective: November 23, 2010

SECTION 1 - PRODUCT IDENTIFICATION

Common Name: Concrete Acid Stain

(As appears on label) **Chemical Family:**

Manufacturer/Supplier: Concrete Coatings Inc

> PO Box 150071 Ogden, UT 84415 1-800-443-2871

Emergency: Chemtrec 1-800-424-9300

Hazard Rating		Scale	
Toxicity Flammability Reactivity	3 0 0	4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant	

SECTION 2 - HAZARDOUS INGREDIENTS

Color	Hazardous Components(s)	CAS No.	Percent By Weight	OSHA PEL	ACGIH TLV
All Colors	Hydrochloric Acid	7647-01-0	<4%	7 mg/m³	7 mg/m³
Caramel	Ferrous Chloride	7758-94-3	Trace	1 mg/m³	1 mg/m³
Olive	Cupric Chloride	7447-39-4	Minor	1 mg/m³	1 mg/m³
	Ferric Chloride	7705-08-0	Minor	1 mg/m³	1 mg/m³
Ebony	Manganese Chloride	7773-01-5	Minor	5 mg/m³	N.E.
	Sodium Dichromate	10588-01-9	Minor	.5 mg/ m ³	.01 mg/ m ³
Jade	Cupric Chloride	7447-39-4	Minor	5 mg/m³	N.E.
	Ferrous Chloride	7758-94-3	Minor	1 mg/ m ³	1 mg/ m ³
Mahogany Coffee Mission Brown	Manganese Chloride	7773-01-5	Minor	5 mg/m³	N.E
	Ferrous Chloride	7758-94-3	Major	1 mg/m³	1 mg/m³
	Sodium Dichromate	10588-01-9	Minor	.5 mg/ m ³	.01 mg/ m ³
Turquoise*	Cupric Chloride	7447-39-4	Minor	1 mg/m³	1 mg/m³
	Phosphoric Acid	7664-38-2	Minor	1 mg/m³	3 mg/m³
Walnut	Sodium Dichromate	10588-01-9	Minor	N/A	N/A
	Manganese Chloride	7773-01-5	Minor	5 mg/m³	N.E
	Ferrous Chloride	7758-94-3	Major	1 mg/m³	1 mg/m³
Amber	Ferrous Chloride	7758-94-3	Major	1 mg/m³	1 mg/m³
Weathered Terracotta	Ferric Chloride	7705-08-0	Major	1 mg/m³	1 mg/m³



VIVIDTM Acid Stain

MATERIAL SAFETY DATA SHEET

Page 2 of 4

Effective: November 23, 2010

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Melting Point: N/A

Specific Gravity (Water = 1): 1.30+/- .03

Vapor Pressure (mm Hg): N/A
Vapor Density (Air = 1): N/A
Solubility in Water: N/A

Evaporation Rate

(Butyl Acetate=1) Slower than Butyl Acetate

Appearance & Odor Dark Liquid with sharp, pungent odor.

PH: 8.0 – 9.0

SECTION 4 - FIRE AND EXPLOSION DATA

Flash Point: Not Established

Flammable Limits: Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Special Fire Fighting

Procedures: Wear self contained breathing apparatus with full face-piece operated in pressure

demand or other positive pressure mode and full body protective clothing when

fighting fire.

Unusual Fire/Explosion

Hazards: Releases Hydrogen Chloride gas when heated. Also reacts with most metals to

release hydrogen gas, which can form explosive mixtures with air.

SECTION 5 - REACTIVITY DATA

Stability: Stable

Conditions to avoid: Avoid contact with strong alkalis, alkali metals.

Incompatible with: N/A

Hazardous decomposition

products: May evolve highly toxic chloride fumes.

Hazardous polymerization: Will not occur.

SECTION 6 HEALTH HAZARD DATA

Carcinogenicity: NO NO NO NO NO NO NO Threshold Limit Value (TLV): 5 ppm

Effects of Overexposure:

Ingestion: Can cause severe tissue destruction. Kidney failure may follow and result in

death.

Inhalation: TLV and OSHA guide is 5ppm Ceiling for Hydrogen Chloride; Severely irritating.

Skin Absorption: Massive overexposure could lead to kidney failure and death.

Eye Contact: Rapidly causes severe burns, possible with permanent impairment of vision.

burning sensation

Emergency and First Aid Procedures



VIVIDTM Acid Stain MATERIAL SAFETY DATA SHEET

Page 3 of 4

Effective: November 23, 2010

Eyes: Flush thoroughly with running water for at least 30 minutes.

Skin: Skin burn likely. An Immediate, continuous, and thorough wash in flowing water

for 30 minutes. Remove clothing immediately. Destroy contaminated shoes.

Inhalation: Move victim to fresh air if effects occur. Call physician and/or transport to medical

facility.

Ingestion: Corrosive. Do not induce vomiting. Give large amounts of water or milk if

available and immediately transport to a medical facility.

NOTE TO PHYSICIAN: Massive overexposure to solutions of this product could lead to kidney

failure and death.

SECTION 7 - SPILL OR LEAK PROCEDURES

If Material Spills or Leaks: Shovel or soak up spilled material into a plastic container and reuse or remove to

approved chemical waste disposal area. Flush area with water, directing runoff to appropriate treatment or disposal container. Never flush to sewer. Major spills

should be reported according to regulations.

Waste Disposal: Dispose of in accordance with local, state and federal regulations.

SECTION 8 - SAFE HANDLING AND STORAGE INFORMATION

Respiratory Protection NIOSH/MSHA approved respirator whenever exposure to vapor/mist is likely to

occur, unless level are below applicable limits. For emergencies, a self-contained

breathing apparatus or full-face respirator is recommended.

Ventilation: Ventilation must be sufficient to control vapors. Breathing of vapors must be

avoided. This material should be confined as far as possible within sealed or covered equipment in which case normal ventilation should be adequate. Special (local) ventilation will be needed in areas where vapors are expected to be vented.

Protective Equipment: Impervious gloves, neoprene or rubber; safety glasses with splash guards or side

shields, chemical goggles, or face shields.

Other Equipment and

Practices: Clean, body covering clothing. Further safety equipment (apron, footwear, etc.)

should be used as necessary to prevent contact with material.

Special Precautions for Handling and Storage:

Prevent all skin and eye contact. Avoid breathing vapors. Re-seal partially used containers. Ensure that all containers are properly labeled to prevent accidental

ingestion. Wash with soap and water before eating, drinking, smoking, or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices. Remove and thoroughly launder contaminated clothing before reuse. Discard contaminated shoes. Store under cool, dry conditions and away from

open flames and high temperatures.

SECTION 9 - SHIPPING INFORMATION



VIVIDTM Acid Stain MATERIAL SAFETY DATA SHEET

Page 4 of 4

Effective: November 23, 2010

DOT Shipping Name: Hydrochloric Acid Solution

DOT Hazard Class: 8 - Corrosive

DOT Reportable Quantity: N/A

USERS RESPONSIBILITY & DISCLAIMER OF LIABILITY: A bulletin such as this cannot be expected to cover all possible situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where precautions – in addition to those described herein are required. Although the information contained herein is based on data considered to be accurate, all materials present unknown health hazards, and should be used with caution and by properly trained personnel. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Any health hazard and safety information should be passed onto your customers or employees, as the case may be. Final suitability of the chemical for each circumstance is the sole responsibility of the end user. No representation or warranties either expressed or implied, of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein, or the chemical to which the information refers. It is the sole responsibility of the end user to comply with all applicable federal, state and local laws and regulations. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed.