

EZ-Wax™ Acrylic Wax

MATERIAL SAFETY DATA SHEET

Page 1 of 4

Effective: April 1, 2018

SECTION 1 - PRODUCT IDENTIFICATION

Common Name: EZ-Wax™

Description: Water based acrylic Wax Manufacturer/Supplier: Concrete Coatings Inc.

PO Box 150071 Ogden, UT 84415 1-800-443-2871

Emergency: Chemtrec 1-800-424-9300

HMIS Hazard Rating		Scale		
Health Flammability Reactivity Special	1 0 0 A/B	4 = Extreme 3 = High 2 = Moderate 1 = Slight 0 = Insignificant		

SECTION 2 – HAZARDOUS INGREDIENTS

Hazardous Components Chemical & Common Names	CAS No.	Percent By Weight	OSHA PEL	OSHA STEL	ACGIH STEL	ACGIH TLV
Diethylene Glycol Monoethyl Ether	111-90-0	10	N.E.	N.E.	N.E.	N.E.
Tributoxyethyl Phosphate	78-51-3	5	N.E.	N.E.	N.E.	N.E.
Acrylic Emulsion Polymer	N/A	5	N.E.	N.E.	N.E.	N.E.
Polyethylene Emulsion	N/A	2	N.E.	N.E.	N.E.	N.E.

SECTION 3 – PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 212 ° F **Freeze Point:** 32 ° F Specific Gravity (Water = 1): 1.028 Vapor Pressure (mm Hg): <30

Vapor Density (Air = 1): Is heavier than air Solubility in Water: Miscible emulsion

Evaporation Rate

(Butyl Acetate=1) < 0.4

Appearance & Odor Milky liquid with a bland odor

PH: 8.3 Viscosity N/A

SECTION 4 – FIRE AND EXPLOSION DATA

Flash Point: Non-flammable aqueous solution Flammable Limits: Lower Explosive Limit: N/A **Upper Explosive Limit**: N/A

Extinguishing Media: Use media proper to the primary cause of fire

Unusual Fire/Explosion

Hazards: None

Special Firefighting

Procedures: None



EZ-Wax™ Acrylic Wax MATERIAL SAFETY DATA SHEET

Page 2 of 4

Effective: April 1, 2018

SECTION 5 – REACTIVITY DATA

Stability: Stable under normal conditions

Conditions to avoid: N/A Incompatible with: N/A

Hazardous decomposition

products: N/A

Hazardous polymerization: Will not occur under normal conditions.

SECTION 6 HEALTH HAZARD DATA

Carcinogenicity: NO IARC: NO OSHA Regulated? NO

Effects of Overexposure:

Inhalation: Prolonged exposure in poorly ventilated area may be slightly irritating to respiratory

tract.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Direct contact may cause slight irritation

Ingestion: May cause gastrointestinal irritation.

Emergency and First Aid Procedures

Eye Contact: Flush eye with large amounts of water for at least 15 minutes and contact

physician if necessary.

Skin Contact: Remove contaminated clothing. Wash skin with soap and water.

Inhalation: Move individual to fresh air immediately if symptoms occur. If breathing becomes

difficult, administer oxygen, and consult physician immediately. If breathing has stopped, apply applicable CPR procedures and contact physician immediately.

Ingestion: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call

a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head

below hips to avoid aspiration of vomitus into lungs.

SECTION 7 – SPILL OR LEAK PROCEDURES

If Material Spills or Leaks: Absorb material with inert media and dispose of in a chemical-waste container.

Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm

sewers and ditches, which leads to waterways.

Waste Disposal: Empty containers may contain product residue and may still be hazardous.

Dispose of in accordance with local, state and federal regulations.



EZ-Wax™ Acrylic Wax MATERIAL SAFETY DATA SHEET

Page 3 of 4

Effective: April 1, 2018

SECTION 8 – SAFE HANDLING AND STORAGE INFORMATION

Respiratory Protection Wear NIOSH/MSHA approved respiratory protection when the product is

applied in a poorly ventilated area or if workplace levels exceed the TLV.

Follow applicable federal, state, and local regulations.

Ventilation: Local exhaust ventilation may be necessary to control any air contaminants

to within their TLV's during the use of this product.

Protective Equipment: Where contact is likely, wear clothing sufficient to prevent wetting of

clothing to minimize contact.

Other Equipment and

Practices: Do not take internally. Wash thoroughly after handling. Avoid breathing

vapors from heated material. Avoid contact with eyes, skin, and clothing.

Special Precautions for

Handling and Storage: Do not allow to freeze. Keep out of reach of children. Keep container closed

when not in use.

SECTION 9 – SHIPPING INFORMATION

DOT Shipping Name: N/A (Non-regulated material)

DOT Hazard Class: N/A

SECTION 10 – REGULATORY INFORMATION

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

------ CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No information is available.

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN

No Proposition 65 chemicals exist in this product.



EZ-Wax™ Acrylic Wax MATERIAL SAFETY DATA SHEET

Page 4 of 4 Effective: April 1, 2018

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

USERS RESPONSIBILITY & DISCLAIMER OF LIABILITY: A bulletin such as this cannot be expected to cover all possible situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where precautions – in addition to those described herein are required. Although the information contained herein is based on data considered to be accurate, all materials present unknown health hazards, and should be used with caution and by properly trained personnel. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Any health hazard and safety information should be passed onto your customers or employees, as the case may be. Final suitability of the chemical for each circumstance is the sole responsibility of the end user. No representation or warranties either expressed or implied, of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein, or the chemical to which the information refers. It is the sole responsibility of the end user to comply with all applicable federal, state and local laws and regulations. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed.

Concrete Coatings Incorporated warrants its products to be of good quality and will replace any product proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Exact color cannot nor will not be guaranteed due to multiple factors including application methods, concrete content, weather, etc. Therefore, except for such replacement, CONCRETE COATINGS INCORPORATED MAKES NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, AND CONCRETE COATINGS INCORPORATED SHALL HAVE NO OTHER LIABILITY WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION, LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. USER ASSUMES ALL RISK AND LIABILITY REGARDING USE AND/OR STORAGE OF THIS PRODUCT. Any claim regarding product defect must be received in writing within ninety (90) days from the date of shipment. No claim will be considered without such written notice or after the specified time interval. The user shall determine the suitability of the products for the intended use and assumes all risk and liability in connection therewith.