



Concrete Coatings, Inc. sealers will bring out the brilliance and luster of all your decorative surfaces. These products help protect against UV, fading, yellowing and untimely wear. Water- and solvent-based sealers are available for any project. With 100% acrylic resins and no fillers, these truly-penetrating sealers provide an excellent sheen.



## Acrylic Sealer Products

Our proprietary formulas allow for an excellent adhesion and greater durability, saving you time and money in maintenance.

### SuperSeal™ 2000 600 VOC Solvent-Based

*\*Flammable*

Please check local regulations for VOC requirements. Concrete Coatings, Inc. SuperSeal™ 2000 is an aromatic acrylic sealer that can be applied to almost any surface: concrete, tile, cementitious overlays and much more. Use SuperSeal™ 2000 for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200 square feet per gallon

- Non-Yellowing
- Gloss "Wet Look" Finish
- Interior/Exterior Use
- Enhances Color

### GemKote™ 400, 350 and 100 VOC Solvent-Based

*\*Flammable*

Please check local regulations for VOC requirements. Concrete Coatings, Inc. GemKote™ uses the same resin as SuperSeal™ 2000 with a VOC content less than 400 g/l, 350 g/l or 100 g/l for local regulations requiring a lower VOC. GemKote™ is an aromatic acrylic sealer that can be applied to almost any surface: concrete, tile, cementitious overlays, natural stone and much more. Use GemKote™ for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200 square feet per gallon

- Non-Yellowing
- Gloss "Wet Look" Finish
- Interior/Exterior Use
- Enhances Color

*\*Flammable products. If used indoors please practice smart safety practices like extinguishing all pilot lights and flame sources.*

### ProSeal™ 18 600 and 100 VOC Solvent-Based

*\*Flammable*

Please check local regulations for VOC requirements. Concrete Coatings, Inc. ProSeal™ 18 is a non-yellowing acrylic solvent-based sealer that aids the curing process of freshly placed concrete. Traditional curing and sealing agents are usually meant as a sacrificial coat and are often required to be removed before applying a finish sealer. ProSeal™ 18 contains the same resin as SuperSeal™ and GemKote™, thereby allowing complete compatibility with these sealers. (Available with a VOC content less than 100 g/l upon request.) Use ProSeal™ 18 for a gloss finish as well as for its UV and stain protection.

Coverage: 150-200 square feet per gallon

- Non-Yellowing
- Excellent Moisture Retention
- Gloss Finish
- Enhances Color

### SuperSeal™ 20WB Water-Based

*\*Non Flammable*

Concrete Coatings, Inc. SuperSeal™ 20WB is a water-based acrylic sealer for general everyday use. This product may be used when a solvent-based sealer cannot due to safety or flammability concerns. A green alternative to solvent-based sealer with a VOC content less than 90 g/l. SuperSeal™ 20WB may be applied to almost any surface: concrete, tile, cementitious overlays and much more. Use SuperSeal™ 20WB for a matte finish as well as for its low VOC's and weatherability.

Coverage: 150-200 square feet per gallon

- No Odor
- Quick Drying
- Low VOC's
- Interior/Exterior Use



Concrete Coatings, Inc. Urethane sealers provide quick dry times and a gloss finish. Water and solvent-based urethanes are available for any project, big or small. Urethane sealers are designed for interior, exterior, commercial and residential use.



SuperSeal™ 20WB  
Photo Courtesy of StainTec

## Urethane Sealer Products

### SuperGlaze™ WBU Water-Based Urethane

*\*Non Flammable*

Concrete Coatings, Inc. SuperGlaze™ WBU can be applied as a single-component water-based urethane for greater durability on non-vehicular applications. This sealer has low VOC content and quick drying properties with low odor. SuperGlaze™ WBU requires a primer prior to application.

Coverage: 300-400 square feet per gallon

- **Excellent Working Time**
- **Excellent Moisture Resistance**
- **Single Component**
- **Quick Drying**

### SuperGlaze™ 3600 Solvent-Based Urethane

*\*Flammable*

Please check local regulations for VOC requirements. Concrete Coatings, Inc. SuperGlaze™ 3600 is a dual-component polyurethane for maximum durability and chemical resistance. Easy to mix, use and apply. Cures hard and is designed to take the abuse of extreme environments. Fast cure time allows for a quick turn-around. SuperGlaze™ 3600 requires a primer prior to application.

Coverage: 200-300 square feet per gallon

- **Color and Gloss Retention**
- **Chemical Resistance**
- **Impact Resistance**

All urethanes require a primer such as Concrete Coatings, Inc. Shield™ 50 and UV Shield™.

## Masonry Sealer Products

### Dri-Look™ Water-Based

*\*Non Flammable*

Concrete Coatings, Inc. Dri-Look™ Masonry Sealer is designed specifically for brick and manufactured stone surfaces to provide an invisible barrier against water and the elements, yet leave the natural look of these surfaces with no visible sheen. Micronized polymers provide all the necessary protection to extend the life of these surfaces.

- **Water Resistant**
- **Invisible Finish**
- **Interior/Exterior Finish**
- **No Odor or Silicone**

For technical assistance please call

**800-443-2871**

[www.ConcreteCoatingsInc.com](http://www.ConcreteCoatingsInc.com)